

constant current driver matrix

constant current																	
type	product code	dimming	cut-out	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link	
DALI dimmable driver 38W constant current multi power	8000-0021	DALI / PUSH	plaster ring Ø57	150 mm	10-54V	350mA	18W	1-2 fx	1-2 fx	1-2 fx	4-14 fx	1-2 fx	-	IP20	146.5 x 44 x 30	↗	
						500mA	27W	-	1-2 fx	1-2 fx	4-14 fx	1-2 fx	-	IP20	146.5 x 44 x 30		
						700mA	38W	-	-	1-2 fx	4-14 fx	-	-	IP20	146.5 x 44 x 30		
						10-36V	1050mA	38W	-	-	-	4-10 fx	-	-	IP20	146.5 x 44 x 30	
1-10V dimmable driver 36W constant current multi power	8000-0022	1-10V	plaster ring Ø57	130 mm	10-54V	350mA	18W	1-2 fx	1-2 fx	1-2 fx	4-14 fx	1-2 fx	-	IP20	129 x 42 x 30	↗	
						500mA	27W	-	1-2 fx	1-2 fx	4-14 fx	1-2 fx	-	IP20	129 x 42 x 30		
						10-51V	700mA	36W	-	-	1-2 fx	4-14 fx	-	-	IP20	129 x 42 x 30	
						10-35V	1050mA	36W	-	-	-	4-10 fx	-	-	IP20	129 x 42 x 30	
non-dimmable driver 42W constant current multi power	8000-0023	not dimmable	plaster ring Ø57	150 mm	3-44V	350mA	15W	1-2 fx	1-2 fx	1-2 fx	2-12 fx	1-2 fx	-	IP20	146.5 x 43 x 30	↗	
						500mA	22W	-	1-2 fx	1-2 fx	2-12 fx	1-2 fx	-	IP20	146.5 x 43 x 30		
						700mA	31W	-	-	1-2 fx	2-12 fx	-	-	IP20	146.5 x 43 x 30		
						3-40V	1050mA	42W	-	-	-	2-10 fx	-	-	IP20	146.5 x 43 x 30	
CASAMBI dimmable driver 38W constant current multi power	8000-0028	Casambi / PUSH	plaster ring Ø57	150 mm	10-54V	350mA	18W	1-2 fx	1-2 fx	1-2 fx	4-14 fx	1-2 fx	-	IP20	146.5 x 44 x 30	↗	
						500mA	27W	-	1-2 fx	1-2 fx	4-14 fx	1-2 fx	-	IP20	146.5 x 44 x 30		
						10-51V	700mA	36W	-	-	1-2 fx	4-14 fx	-	-	IP20	146.5 x 44 x 30	
						10-36V	1050mA	38W	-	-	-	4-10 fx	-	-	IP20	146.5 x 44 x 30	
constant current multipower																	
type	product code	dimming	cut-out	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link	
DALI / 0-10V dimmable driver 60W constant current multi power	8000-0026	DALI/0-10V/PUSH	remote	-	20-112V	350mA	39W	2-5 fx	2-5 fx	2-5 fx	10-30 fx	2-5 fx	-	IP20	124 x 79 x 22	↗	
						500mA	56W	-	2-5 fx	2-5 fx	10-30 fx	2-5 fx	-	IP20	124 x 79 x 22		
						2-86V	700mA	60W	-	-	2-4 fx	10-25 fx	-	-	IP20	124 x 79 x 22	
deep dim																	
type	product code	dimming	cut-out	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link	
DALI deep dim driver 20W constant current 350mA	8000-0031	DALI	plaster ring Ø57	120 mm	2-40V	350mA	20W	1-2 fx	1-2 fx	1-2 fx	1-10 fx	1-2 fx	-	IP20	151 x 43 x 28	↗	
DALI deep dim driver 20W constant current 500mA	8000-0030	DALI	plaster ring Ø57	120 mm	2-40V	500mA	20W	-	1-2 fx	1-2 fx	1-10 fx	1-2 fx	-	IP20	151 x 43 x 28		
DALI deep dim driver 20W constant current 700mA	8000-0027	DALI	plaster ring Ø57	120 mm	2-28V	700mA	20W	-	1 fx	1-2 fx	1-6 fx	-	-	IP20	151 x 43 x 28		

constant current driver matrix

low voltage

type	product code	dimming	cut-out	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link
DALI dimmable power converter 48V to 350-700mA	8000-0037	DALI / PUSH	plaster ring Ø38	90 mm	2-19V	350mA	13W	1 fx	1 fx	1 fx	1-5 fx	1 fx	-	IP20	82 x 27 x 16.5	↗
						500mA	13W	-	1 fx	1 fx	1-5 fx	1 fx	-	IP20	82 x 27 x 16.5	
						700mA	13W	-	-	1 fx	1-5 fx	-	-	IP20	82 x 27 x 16.5	
			2-43V	350mA	29W	1-2 fx	1-2 fx	1-2 fx	1-10 fx	1-2 fx	-	IP20	82 x 27 x 16.5			
				500mA	29W	-	1-2 fx	1-2 fx	1-10 fx	1-2 fx	-	IP20	82 x 27 x 16.5			
				700mA	29W	-	-	1-2 fx	1-10 fx	-	-	IP20	82 x 27 x 16.5			

constant current high current micro

type	product code	dimming	cut-out	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link
DALI / push dimmable driver 52W for micro short - 1050mA	8000-0062	DALI	remote	-	2-55V	1050mA	-	-	-	-	1-15 fx	-	-	IP20	153 x 76 x 31	↗
DALI / push dimmable driver 52W for micro long - 1400mA	8000-0063	DALI	remote	-	2-55V	1400mA	-	-	-	-	1-10 fx	-	-	IP20	153 x 76 x 31	↗

phase dimming

type	product code	dimming	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link	
TRIAC dimmable driver 7W constant current 350mA	8000-0034	TRIAC	plaster ring Ø57	130 mm	3-20V	350mA	7W	1 fx	1 fx	1 fx	2-5 fx	1 fx	-	IP20	101.5 x 49 x 29	↗
TRIAC dimmable driver 10W constant current 500mA	8000-0035	TRIAC	plaster ring Ø57	130 mm	3-20V	500mA	10W	-	1 fx	1 fx	2-5 fx	1 fx	-	IP20	101.5 x 49 x 29	↗
TRIAC dimmable driver 14W constant current 700mA	8000-0046	TRIAC	plaster ring Ø57	130 mm	3-20V	700mA	14W	-	-	1 fx	2-5 fx	-	-	IP20	123.5 x 33 x 20	↗
TRIAC dimmable driver mini 10W constant current 350mA	8000-0043	TRIAC	plaster ring Ø57	60 mm	15-29V	350mA	10W	1 fx	1 fx	1 fx	-	1 fx	-	IP20	58 x 36 x 20	↗
TRIAC dimmable driver mini 10W constant current 500mA	8000-0044	TRIAC	plaster ring Ø57	60 mm	10-20V	500mA	10W	-	1 fx	1 fx	-	1 fx	-	IP20	58 x 36 x 20	↗

constant current driver matrix

outdoor																
type	product code	dimming	cut-out	installation depth*	forward voltage	current	max. wattage	10° pc	20-60° pc	15-60° glass	micro	wallwash	10° outdoor	IP	dimensions (mm)	link
IP68 DALI dimmable driver 38W constant current 350mA	8000-0050	DALI / PUSH	remote	-	10-54V	350mA	18W	1-2 fx	1-2 fx	1-2 fx	-	-	1-4 fx	IP68	127 x 47 x 28	↗
IP68 DALI dimmable driver 38W constant current 500mA	8000-0039	DALI / PUSH	remote	-	10-54V	500mA	27W	-	1-2 fx	1-2 fx	-	-	1-4 fx	IP68	127 x 47 x 28	
IP68 DALI dimmable driver 38W constant current 700mA	8000-0051	DALI / PUSH	remote	-	10-54V	700mA	38W	-	-	1-2 fx	-	-	1-4 fx	IP68	127 x 47 x 28	
IP68 non-dimmable driver IPR2 17W constant current 350mA	8000-0054	Non DIM	remote	-	5-49V	350mA	17W	1-2 fx	1-2 fx	1-2 fx	-	-	1-3 fx	IP68	122 x 54 x 26 mm	
IP68 non-dimmable driver IPR2 24W constant current 500mA	8000-0055	Non DIM	remote	-	5-49V	500mA	24W	-	1-2 fx	1-2 fx	-	-	1-3 fx	IP68	122 x 54 x 26 mm	
IP68 non-dimmable driver IPR2 30W constant current 700mA	8000-0056	Non DIM	remote	-	5-43V	700mA	30W	-	-	1-2 fx	-	-	-	IP68	122 x 54 x 26 mm	
IP68 DC mini jolly 1-10V dimmable driver IPR2 16W 350mA	8000-0057	1-10V	remote	-	2-46V	350mA	16W	1-2 fx	1-2 fx	1-2 fx	-	-	1-3 fx	IP68	122 x 54 x 26 mm	
IP68 DC mini jolly 1-10V dimmable driver IPR2 20W 500mA	8000-0058	1-10V	remote	-	2-40V	500mA	20W	-	1-2 fx	1-2 fx	-	-	1-3 fx	IP68	122 x 54 x 26 mm	
IP68 DC mini jolly 1-10V dimmable driver IPR2 17W 700mA	8000-0059	1-10V	remote	-	2-24V	700mA	17W	-	-	1 fx	-	-	-	IP68	122 x 54 x 26 mm	

constant current driver matrix

